


Technical Data Sheet

Carcoat Repella O4

Grease resistant one side double layer clay coated calendered kraft paper with a functional treatment on the back side



Features

- Oil and grease treatment without PFOA and PFOS
- Very good oil and grease barrier (Kit Test)
- Smooth surface for excellent print results
- Excellent runnability

Specifications

Edition:	February	2020

Target values	Methods	Units			
at 23 $^\circ\text{C}$ / 50% r. H. for general guidance only					
Substance	ISO 536	g/m ²	70	80	90
Thickness	ISO 534	μ m	67	74	84
Tensile Strength MD	DIN EN 1924-2	N/15mm	70	75	80
Tensile Strength CD	DIN EN 1924-2	N/15mm	40	45	50
Brightness R457	DIN 53145	%	83	83	83
Gloss Lehmann 75°	ISO 8254-1	%	62	62	62
Roughness PPS H10 coated side	ISO 8791-4	μm	1.3	1.2	1.2
Kit Test coated side	TAPPI UM 559	n°	8	8	8
Kit Test back side	TAPPI UM 559	n°	7	7	7

Print

- Offset, Rotogravure, Flexo
- Letterpress
- Hot-stamping

Converting

• Lamination to release base paper

Compliance

- Regulation EC 1935/2004
- Regulation EC 2023/2006
- Directive 94/62/EC and amendments

Format

- Reel
- Sheet

End Uses

- Oil and grease self-adhesive labels for oil bottles
- Outside wraps of oil and greasy products
- Outside paper for multilayer pet food bags, in combination with brown kraft paper and plastic film
- Italian Law D.M. of 21/03/1973 and amendments
- FDA
- BfR XXXVI

Important: The information given is based on our best knowledge at the time of printing. It is given in good faith and represents neither implied nor actual guarantee and no legal warranty for specific properties or for suitability for a specific application. Responsibility for testing the suitability of the product for specific applications lies with the purchaser. We shall be pleased to aid customers with such tests where possible. Should a claim be taken into consideration, liability will, under no circumstances exceed the value of the goods supplied. SAPPI Italy Operations S.p.a. guarantees the impeccable quality of its goods in accordance with agreed specifications and their standard conditions of sale and delivery.